

SERIAL BRIDGE MODULE WITH SD CARD AND WEB SERVER FUNCTION

SimpleHome Web Server for local or remote management of the SimpleHome system. Allows system management directly from internet browser, tablet or smartphone. Can be used to control lights, blinds, climate, loads, anti-intrusion devices, etc.. Allows programming of weekly timers, scenarios or operating logic of the inputs and outputs of an automation or anti-intrusion system. The configuration is imported directly from the programming software via SD card. The new graphic interface is fully compatible with the Planux Manager and Mini Touch supervisors. Connections: SimpleHome bus, RS232, RS485, Ethernet - Power supply: 12/24Vdc - Dimensions: 4 DIN modules.



General specifications

DIN rail mounted: **Yes**

Functions

Automation management: **Yes**

Climate management: **Yes**

Fancoil management: **Yes**

Lights management: **Yes**

Scenario management: **Yes**

Hardware specifications

Removable terminals: **Yes**

General info

Product height (mm): **90**

Product width (mm): **62**

Product depth (mm): **72**

Operating temperature (°C): **-5÷40**

Compatibility

Home automation family: **Yes**

Mounting/Installation

DIN modules (no.): **4**

Connectivity

No. of Simplehome buses: **1**

DATA SHEET

Type of connections/ports:

1 LAN, 1 RS485, 1 BUS Home

Electrical specifications

Maximum current absorption (mA):

200