

4.3" ICONA MANAGER SUPERVISOR, VIP SYSTEM, WHITE

Icona Manager 4.3• Touch Screen with integrated ViP system door entry monitor, SimpleHome home automation system management, SimpleSafe intruder alarm system management. Capacitive 4.3• touch screen display with gesture detection for easy menu navigation. With Sensitive Touch controls for lock-release, audio on, swipe for self-ignition button, privacy service and 3 other controls for programmable functions, door open indicator LED and new messages. Standard floor door call and call repetition management, with alarm and panic inputs and micro SD Card. Ringtone and video mail function absent message can be configured. Integrated temperature sensor. RFID reader for activating entrance and exit scenarios. Communication BUS power supply (12-24Vdc). Supervisor for controlling lights, rolling blinds, automated opening, zoned climate control with customised scheduling, garden sprinkler management, utility consumption display (electricity, water gas etc.), electric load disconnection management, intruder alarm system management and control, camera viewing on IP network. White. Dimensions 142.5x147x23mm. Protrusion from wall with flush-mounted box (art. 6117) 25 mm. Max. draw 6W.

**General specifications**

Sensitive Touch technology:	Yes
Touch screen display:	Yes
Display size (inches):	4,3" 16/9
Product color:	Bianco
Backlighting color:	Bianca
Display resolution (H x V):	480x272 pixel
Flush-mounted:	Scatola art. 6117
Wall-mounted:	Supporto art.6620

Software/firmware specifications

No. scenarios:	50
Weekly programming:	Yes
IP assignment:	AUTO IP, DHCP, STATIC

Functions

Floor door call:	Yes
Multi-speed control (fan coil) with temperature sensor:	Yes
Multi-speed control (cmv) with integrated humidity sensor:	Yes
Alarm function:	Yes
Bridging function from automation to anti-intrusion:	Yes
Switchboard call function:	Yes
Floor door call function:	Yes
Actuator control function:	Yes
Privacy conversation function:	Yes
Induction loop function:	Yes

DATA SHEET

Intercom function:	Yes
Privacy function:	Yes
Key button function:	Yes
Hands-free function:	Yes
Full Duplex hands-free function:	Yes
Temperature and humidity control for other climate zones:	Yes
Automation management:	Yes
Loads management:	Yes
Climate management:	Yes
Consumption management:	Yes
Lights management:	Yes
Integrated sensor heating/cooling control:	Yes
Scenario management:	Yes
Scheduling management:	Yes
Anti-intrusion system management:	Yes
Audio distribution system management:	Yes
Video entry system management:	ViP
Temperature and humidity control:	Yes
Timing management:	Yes
Integrated sensor humidifying/dehumidifying control:	Yes
Maximum number of scenarios managed:	70
Daily/weekly programming:	Yes
Integrated sensor local temperature regulation:	Yes
Loudspeaker volume control:	Yes
Ringtone volume control:	Yes
SD or microSD card included for consumption and configuration:	Yes
Integrated sensor status display:	Yes

Hardware specifications

Removable terminals:	Yes
----------------------	-----

General info

Product height (mm):	142,5
Product width (mm):	145,5
Product depth (mm):	12 (sporgenza dalla parete)
Operating temperature (°C):	-5÷50
Self-ignition:	Yes
Customisable ringtone:	Yes

Compatibility

Video door entry family:	Yes
Antintruder family:	Yes
Home automation family:	Yes

DATA SHEET

Mounting/Installation

Flush-mounted box type:	Art.6117
Desk base-mounted:	Yes

Audio/video specifications

B/W or colour display:	Color
Audio system:	Yes
Audio/video system:	Yes
Type of display:	TFT

Connectivity

No. of Simplehome buses:	1
Ethernet ports:	1
RS485 ports:	1

Technical specifications

Network connection:	Yes
SimpleHome home automation bus connection:	Yes
SimpleSafe anti-intrusion bus connection:	Yes
Proximity reader RFID:	Yes
Integrated temperature sensor:	Yes
Integrated humidity sensor:	Yes
Integrated sensor temperature range measured:	5-30°C
Integrated sensor temperature reading resolution:	0,1°C
Integrated sensor set temperature resolution:	0,1°C
On-board output for boiler control:	No
On-board outputs for multi-speed control (fan coil):	No
Integrated sensor humidity reading range:	0-100%
Integrated sensor humidity setting resolution:	1%
Power supply voltage:	12/24Vdc
Max. absorption:	6W

Electrical specifications

Absorption:	6W
-------------	----