DATA SHEET

Main specifications

Signal/noise ratio (dB):

Loudspeaker volume control:

Video output:

cod. 3005XV

316 ANALOG AUDIO/VIDEO ENT. PANEL, 5 BUTTONS. SBC SYSTEM

Simplebus Color system audio-video unit with terminal block complete with front-adjustable wide-angle 1/4? color camera and LED camera illumination. Complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. Audio-visual indications for disabled individuals assistance request can be activated via programming. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lockrelease function (3A), plus C, NC, NO 10A relay contacts. Compatible with all SBTOP functions and products. Allows call addressing for up to 120000 users. Timed lock-release input and door open indication.



1 Vpp / 75 PAL Software/firmware specifications Camera pixels (H x V): 500x582 **Hardware specifications** Vandal Resistant IK: IK08 DDE function: Yes Total buttons: Sensitive Touch technology: Yes **Functions**

Product depth (mm): Operating temperature (°C): -25/55

Compatibility

Simplebus Top system: Yes Simplebus Color system: Yes

Yes

Mounting/Installation

Flush-mounted: Yes

Audio/video specifications

Horizontal resolution (TVL): 420



DATA SHEET

Audio/video system:

Technical properties
Sensitivity (lux):
Type of camera:

COLOR

Electrical specifications
Maximum current absorption (mA):
450

