

316 ANALOG AUDIO/VIDEO ENT. PANEL, 6 BUTTONS. SBC SYSTEM

Simplebus Color system audio-video unit with terminal block complete with front-adjustable wide-angle 1/4" color camera and LED camera illumination. Complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. Audio-visual indications for disabled individuals assistance request can be activated via programming. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lockrelease function (3A), plus C, NC, NO 10A relay contacts. Compatible with all SBTOP functions and products. Allows call addressing for up to 120000 users. Timed lock-release input and door open indication.

**Main specifications**

| | |
|--------------------------|----------------|
| Signal/noise ratio (dB): | 48 |
| Video output: | 1 Vpp / 75 PAL |

Software/firmware specifications

| | |
|------------------------|---------|
| Camera pixels (H x V): | 500x582 |
|------------------------|---------|

Hardware specifications

| | |
|-----------------------------|------|
| Vandal Resistant IK: | IK08 |
| DDE function: | Yes |
| Total buttons: | 6 |
| Sensitive Touch technology: | Yes |

Functions

| | |
|-----------------------------|-----|
| Loudspeaker volume control: | Yes |
|-----------------------------|-----|

General info

| | |
|-----------------------------|--------|
| Product depth (mm): | 60 |
| Operating temperature (°C): | -25/55 |

Compatibility

| | |
|-------------------------|-----|
| Simplebus Top system: | Yes |
| Simplebus Color system: | Yes |

Mounting/Installation

| | |
|----------------|-----|
| Flush-mounted: | Yes |
|----------------|-----|

Audio/video specifications

| | |
|------------------------------|-----|
| Horizontal resolution (TVL): | 420 |
|------------------------------|-----|

DATA SHEET

Audio/video system: Yes

Technical properties

Sensitivity (lux): 1

Type of camera: COLOR

Electrical specifications

Maximum current absorption (mA): 450