DATA SHEET

COD. 3007XV

316 ANALOG AUDIO/VIDEO ENT. PANEL, 7 BUTTONS. SBC SYSTEM

Simplebus Color system audio-video unit with terminal block complete with front-adjustable wide-angle 1/4? color camera and LED camera illumination. Complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. Audio-visual indications for disabled individuals assistance request can be activated via programming. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lockrelease function (3A), plus C, NC, NO 10A relay contacts. Compatible with all SBTOP functions and products. Allows call addressing for up to 120000 users. Timed lock-release input and door open indication.



Main specifications Signal/noise ratio (dB): 48 Video output: 1 Vpp / 75 PAL

Software/firmware specifications

Camera pixels (H x V):

Hardware specifications

Vandal Resistant IK:	IK08	
DDE function:	Yes	
Total buttons:	7	
Sensitive Touch technology:	Yes	

Functions

Loudspeaker volume control:	: Y	es

General info

Product depth (mm):	60
Operating temperature (°C):	-25/55

Compatibility

Simplebus Top system:	Yes
Simplebus Color system:	Yes

Mounting/Installation

riusii-iilouliteu.	Flush-mounted:	'es
--------------------	----------------	-----

Audio/video specifications

Horizontal resolution (TVL):	420
------------------------------	-----



DATA SHEET

Audio/video system:

Technical properties
Sensitivity (lux):
Type of camera:

COLOR

Electrical specifications
Maximum current absorption (mA):
450

