

DATA SHEET

COD. **3010XV**

316 ANALOG AUDIO/VIDEO ENT. PANEL, 10 BUTTONS. SBC SYSTEM

Simplebus Color system audio-video unit with terminal block complete with front-adjustable wide-angle 1/4" color camera and LED camera illumination. Complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. Audio-visual indications for disabled individuals assistance request can be activated via programming. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lockrelease function (3A), plus C, NC, NO 10A relay contacts. Compatible with all SBTOP functions and products. Allows call addressing for up to 120000 users. Timed lock-release input and door open indication.



Main specifications

Signal/noise ratio (dB):	48
Video output:	1 Vpp / 75 PAL

Software/firmware specifications

Camera pixels (H x V):	500x582
------------------------	---------

Hardware specifications

Vandal Resistant IK:	IK08
DDE function:	Yes
Total buttons:	10
Sensitive Touch technology:	Yes

Functions

Loudspeaker volume control:	Yes
-----------------------------	-----

General info

Product depth (mm):	60
Operating temperature (°C):	-25/55

Compatibility

Simplebus Top system:	Yes
Simplebus Color system:	Yes

Mounting/Installation

Flush-mounted:	Yes
----------------	-----

Audio/video specifications

Horizontal resolution (TVL):	420
------------------------------	-----

The technical specifications are subject to variations without warning

DATA SHEET

Audio/video system: Yes

Technical properties

Sensitivity (lux): 1

Type of camera: COLOR

Electrical specifications

Maximum current absorption (mA): 450