

DATA SHEET

COD. 3070B

SIMPLEBUS DIGITAL CALL MODULE, VANDALCOM SERIES

Made using a double 2.5 mm stainless steel plate, complete with keypad with 12 backlit stainless steel buttons, 16-character alphanumeric display for viewing call codes and user interaction messages (busy, etc.). Also functions as an electronic key code with a possible 1000 different 6-digit command codes. The device controls the on-board relay of art. 3062. Dimensions: 106x106x56 mm. From IR10 it is compatible with all SBTOP products and functions. It can be used for the call addressing of up to 120000 users.



Main specifications

Backlighting colour: LED GREEN

Software/firmware specifications

No. user codes: 1500

No. of storable users: 1500

Hardware specifications

Vandal Resistant IK: Yes

Customisable housing: No

DDE function: No

Total buttons: 12

Sensitive Touch technology: No

Functions

Key button function: Yes

General info

Product height (mm): 106

Product width (mm): 106

Product depth (mm): 56

Product colour: GREY

Operating temperature (°C): -25/55

Intrastat code: 85176920

Compatibility

Simplebus Top system: Yes

DATA SHEET

Simplebus Color system:	Yes
Simplebus 2 system:	Yes
Vip system:	Yes

Mounting/Installation

Flush-mounted:	Yes
Wall-mounted:	Yes
Surface-mounted:	Yes

Audio/video specifications

Display resolution (H x V):	16x2 characters
Audio system:	Yes
Audio/video system:	Yes
Type of display:	Alphanumeric

Connectivity

Type of connections/ports:	RS232, RS485
RS232 ports:	1
RS485 ports:	1

Electrical specifications

Maximum current absorption (mA):	100
----------------------------------	-----

Packaging

Single pack height (mm):	88
Single pack width (mm):	113
Single pack weight (Kg):	0,767
Single pack depth (mm):	111
Single pack volume (dm3):	1,104