






NVR / Hybrid NVR

MEGAPIXEL REAL-TIME NVR

		25CH NVR	16CH NVR		9CH NVR	4CH NVR
						
Model		HNR-25DF	HNR-16DF	HNR-16EE	HNR-09EE	HNR-04EE
System						
OS		Embedded Linux	Embedded Linux	Embedded Linux	Embedded Linux	Embedded Linux
Connector	Ethernet	RJ-45 x2, 10/100/1000 Mbps	RJ-45 x2, 10/100/1000 Mbps	RJ-45 x1, 10/100/1000 Mbps	RJ-45 x1, 10/100/1000 Mbps	RJ-45 x1, 10/100/1000 Mbps
	Throughput	100M	100M	64M	45M	24M
	VGA Output	D-SUB output	D-SUB output	D-SUB output	D-SUB output	D-SUB output
	HDMI output	HDMI output	HDMI output	HDMI output	HDMI output	HDMI output
	USB 2.0	Front : 2 ports	Front : 2 ports	Front : 2 ports	Front : 2 ports	Front : 2 ports
Power		100~240V, 50~60 Hz	100~240V, 50~60 Hz	DC 12V, 5A	DC12V, 5A	DC12V, 5A
Video and Audio						
Support IP Cam Resolution		5M	5M	5M	5M	5M
Video Input		25 channels	16 channels	16 channels	9 channels	4 channels
Audio Input		25 channels	16 channels	4 channels	4 channels	4 channels
NVR Functions						
Screen Split Control		1, 4, 9, 16, 25	1, 4, 9, 16	1, 4, 9, 16	1, 4, 9	1, 4
Pre Recording		10 sec	10 sec	10 sec	10 sec	10 sec
Watermark		Support	Support	Support	Support	Support
Searching and Playback						
Date/ Time / Event Search		Selectable on the calendar	Selectable on the calendar	Selectable on the calendar	Selectable on the calendar	Selectable on the calendar
Log Search		Through the log data to find the video event / time	Through the log data to find the video event / time	Through the log data to find the video event / time	Through the log data to find the video event / time	Through the log data to find the video event / time
Backup Type		USB	USB	USB	USB	USB
Remote Client Software						
Monitoring Environment		Hunt CMS, Iprosecu M. V2 for I phone / I pad , Iprosecu A.M. V2 for Android phone / Android pad, Web site	Hunt CMS, Iprosecu M. V2 for I phone / I pad , Iprosecu A.M. V2 for Android phone / Android pad, Web site	Hunt CMS, Iprosecu M. V2 for I phone / I pad , Iprosecu A.M. V2 for Android phone / Android pad, Web site	Hunt CMS, Iprosecu M. V2 for I phone / I pad , Iprosecu A.M. V2 for Android phone / Android pad, Web site	Hunt CMS, Iprosecu M. V2 for I phone / I pad , Iprosecu A.M. V2 for Android phone / Android pad, Web site
IP Cam Live View		25 Channels	16 Channels	16 Channels	9 Channels	4 Channels
System Monitoring and Recovery						
Monitoring		Watchdog	Watchdog	Watchdog	Watchdog	Watchdog
Alarm						
Alarm Input		8 inputs	8 inputs	8 inputs	8 inputs	8 inputs
Alarm Output		1 outputs	1 outputs	1 outputs	1 outputs	1 outputs
Peripheral Devices						
Audio In		3.5 Ø Phone Jack	3.5 Ø Phone Jack	3.5 Ø Phone Jack	3.5 Ø Phone Jack	3.5 Ø Phone Jack
Audio Out		3.5 Ø Phone Jack	3.5 Ø Phone Jack	3.5 Ø Phone Jack	3.5 Ø Phone Jack	3.5 Ø Phone Jack
RS-485		2- pin terminal	2- pin terminal	2- pin terminal	2- pin terminal	2- pin terminal
Storage & Backup Device						
Internal HDD Support		SATA HDD x 9 SATA HDD x 4	SATA HDD x 9	SATA HDD x 4	SATA HDD x 4	SATA HDD x 4
External USB Backup Device		USB x2	USB x2	USB x2	USB x2	USB x2
E-SATA		x1	x1	x1	x1	x1
Networking						
Type		Static/ DHCP/ PPPoE/DDNS	Static/ DHCP/ PPPoE/DDNS	Static/ DHCP/ PPPoE/DDNS	Static/ DHCP/ PPPoE/DDNS	Static/ DHCP/ PPPoE/DDNS
Environment						
Operating Temp.		0 - 45°C / 32~113° F	0 - 45°C / 32~113° F	0 - 45°C / 32~113° F	0 - 45°C / 32~113° F	0 - 45°C / 32~113° F
Physical						
Color		Black	Black	Black	Black	Black
Dimensions (W x H x D)		430 x 88 x 422 mm	430 x 88 x 422 mm	360 x 60 x 311 mm	360 x 60 x 311 mm	360 X 60 X 311mm

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE