

GTI-F0811E

LAN & Power over Ethernet Extender



- IEEE 802.af, IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX
- 1-port PoE Splitter (PD) and 1-Port PoE injector (PSE)
- No extra power required
- need around 2W per extension
- Metal housing against vandalism

SPECIFICATIONS

Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
Interfaces	1 x PD (Data + Power in), 1 x PSE (Data+Power out)
Filtering/Forwarding Rate	10Mbps port - 14,880 pps 100Mbps port - 148,800 pps
Transmission Media	100BaseTX Cat. 5/5e/6 UTP/STP, up to 100m
LED Indicators	PoE IN: PD (Link), Port 2: PD Link/Act, PoE Out: Link, Port 1: PSE Link/Act

SPECIFICATIONS

Supply Voltage	PoE IN/OUT (IEEE 802.3af)
Operating Temperature	0°C ~ +55°C
Storage Temperature	-20°C ~ +90°C
Humidity	10 ~ 90% no condensation
Certification	FCC Class A, CE
Power Consumption	2 W
Weight	0.252 kg
Dimensions w*h*d	130 x 24 x 77 mm