

DS-2CE16D0T-IT3E HD 1080p PoC EXIR Bullet Camera



Key Features

- 2.0 megapixel high-performance CMOS
- HD analog output, up to 1080p resolution
- 2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm, 16 mm fixed focal lens
- True Day/Night
- EXIR 2.0, up to 40 m IR distance
- IP66
- PoC.af
- Up the Coax (HIKVISION-C)




Specification

| Camera | |
|--------------------------|-------------------------------------------------------------------------------------------------|
| Image Sensor | 2.0megapixelprogressive scan CMOS |
| Signal System | PAL/NTSC |
| Frame Rate | PAL: 1080p@25fps NTSC: 1080p@30fps |
| Effective Pixels | 1920(H) × 1080(V) |
| Min. illumination | 0.01 Lux@(F1.2,AGC ON),0 Lux with IR |
| Shutter Time | PAL: 1/25s to 1/50,000s NTSC: 1/30 s to 1/50, 000 s |
| Lens | 2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm, 16 mmfixed focal lens |
| Horizontal Field of View | 103.55° (2.8 mm), 82.63° (3.6 mm), 54.38° (6 mm), 37.96° (8 mm), 24.36° (12 mm), 18.92° (16 mm) |
| Lens Mount | M12 |
| Day & Night | IR cut filter |
| Angle Adjustment | Pan:0° to360°, Tilt:0° to 180°, Rotate:0° to360° |
| Synchronization | Internal synchronization |
| S/N Ratio | >62dB |
| Interface | |
| Video Output | 1 HD analog output/1Vp-p composite output (75Ω/BNC) |
| General | |
| Operating Conditions | -40 °C to 60 °C (-40 °F to 140 °F),humidity: 90% or less (non-condensation) |
| Power Supply | 12 VDC±30%/PoC.af |
| Power Consumption | Max. 4W |
| Ingress Protection | IP66 |
| Material | Metal& Plastic |
| IR Range | Up to 40m |
| Communication | Up the coax, Protocol: HIKVISION-C(TVI output) |
| Dimensions | 86.7 mm ×81.6 mm ×226 mm(3.4"×3.2"×8.9") |
| Weight | Approx.430 g (0.95lb) |

Order Models

DS-2CE16D0T-IT3E

Dimension



Accessory



DS-1280ZJ-XS
Junction Box



DS-1H18
Video Balun

Distributed by



HIKVISION

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (10) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com