

# LINEA 11

## Camera Housing

### **KIT11A**

*Weatherproof housing, Heater with thermostat, Blower kit, Wall bracket, RAL9002*



### **USER FRIENDLY**

*All opening and closing operations can be done with just one tool.*

### **FULL OPTIONAL**

*Wide range power supply, heater and blower kit can be factory installed.*

### **FOR IP AND ANALOG CAMERAS**

*State of the art technology to meet most severe requirements for IP and analog cameras*

### **SUITABLE FOR OUTDOOR AND INDOOR**

*Weatherproof rated, the integrated sunshield and the large window guarantee clear images and no vignetting*



**tekno system**<sup>®</sup>  
Italian design for CCTV since 1979

Tekno System S.p.A.  
Via Rostoncello, 1 - 36010 Carrè - Italy  
Phone: +39 0445 314324 | Fax: +39 0445 314319  
Email: [info@tekno-system.eu](mailto:info@tekno-system.eu) | Web: [www.tekno-system.eu](http://www.tekno-system.eu)

rev. 030310

Page 1 / 4







## TECHNOLOGY HIGHLIGHTS

Indoor / Outdoor Installations Patented Slide and Hang System IP66 (EN60529)	Extruded Aluminium Body ABS Front and Back Caps Integrated Sunshield	Designed for IP and analog cameras Glass Window
--	--	--





## MODELS

ORDER CODE	Wall bracket	Sunshield	IP Rate	Heater	Blower	Power supply	Wide range power supply
KIT11A/300	●	●	IP66				
KIT11A/300 + HT	●	●	IP66	●			
KIT11A/300 + HT + V11/230; V11/24	●	●	IP44	●	●		
KIT11A/300 + HT + ALWR	●	●	IP66	●			●
KIT11A/300 + HT + ALWR + V11/12	●	●	IP44	●	●		●
KIT11A/300 + HT + AL11/12; AL11/24	●	●	IP66	●		●	

## ACCESSORIES

<b>HT</b>	Heater with thermostat 12-24V or 100-240V	
<b>V11/12</b>	Blower kit with thermostat 12VDC; 24V~; 230V~	
<b>ALWR</b>	Wide range power supply	
<b>AL12, AL24</b>	Power Supply 12V or 24V~	
<b>EL</b>	Camera height adjustment kit	
<b>BW9H6</b>	Wall mount bracket	

## RELATED PRODUCTS

<b>PA/1</b>	Pole mount adapter for one bracket	
<b>PA/2</b>	Pole mount adapter for two brackets	
<b>CM</b>	Corner mount adapter	
<b>R2B50</b>	Bracket for illuminators	



# SPECIFICATION

## General

- Extruded aluminium body
- ABS UV resistant front and back caps
- Integrated Sunshield
- RAL9002 Polyester powder coating
- Supplied with: instruction manual, silicagel bag, ¼" camera fixing screw, BW9H6 wall bracket and swivel head

## Mechanical

- Internal usable area: 85 x 75mm (3.34 x 2.95in)
- Internal usable length: 252mm (9.92in)
- Usable Glass Windows 83,5 x 63,6mm (3.28 x 2.50in) Horizontal / Vertical max size
- 3mm-Thick glass
- 2 removable M16x1,5 cable glands
- Zinc coated screws

## Electrical

- Heater Thermostat  $T_{on}$  15°C (59°F)  $\pm$  5°C  $T_{off}$  22°C (71.6°F)  $\pm$  4°C
- Heater PTC 100-240V~ 40W
- Heater PTC 12-24V~ 20W
- Blower Thermostat  $T_{on}$  37°C (98.6°F)  $\pm$  4°C  $T_{off}$  27°C(80.6°F)  $\pm$  3°C
- Blower with double air filter, consumption 1W
- Camera power supply unit:  
ALWR: Vin 88-264V~ 47/63Hz Vout 12VDC 2,1A;  
AL12 Vin 230V~ 50Hz Vout 12VDC 400mA;  
AL24 Vin 230V~ 50Hz Vout 24V~ 50Hz 400mA;

## Environment

- Indoor / Outdoor applications
- Temperature range with heater: -20°C (-4°F) up to +50°C (+122°F)
- IP66 weatherproof rating (according to EN60529)
- CE according to EN61000-6-3, EN60950, EN50130-4
- RoHS compliant

Technical data and product features might be modified without any warning.



Slide & hang system



Ceiling Mounting KIT 11 AC



