



## ● FEATURES

1. High efficiency cooling structure aluminium case, IP66
2. Dual voltage(AC24V/DC12V)
3. 55 PCs IR LED
4. Switch on/off automatically by photocell
5. Available IR in (Outdoor): 25M, 120°

**Remark: Non-regulative adaptor may cause camera damaged.**

## ● ACCESSORIES

Illuminator	X1
User Manual	X1
Screw	X4
Plastic-Conical-Anchor	X4
Hexagonal Wrench	X1
Mounting Drawing Paper	X1

● **SPECIFICATION**

Item	LIR-CS32
IP rating	IP66
IR LED	55PCs IR LED
Wave Length	850nm
IR Projecting Angle	120°
Emissive Power	5W
Available IR Distance	25M(81.97ft)
Control	CDS/10Lux
Power Supply	DC12V±10%/AC24V±10%
Current Consumption	DC380mA/AC500mA
Dimension	180×130×90mm(0.59x0.43x0.30ft)
Weight	750g
Storage Temperature	-30~+60°C (-22~+140°F)
Operating Temperature	-30~+40°C (-22~+104°F)

● **PACKAGE**

Weight .....750g  
 Dimension ..... 180×130×90mm  
 Quantity per carton .....16PCs  
 Dimension of carton.....450×350×520mm  
 Weight of carton.....13.5KGs